







## Speed, Performance, Value - Perfect Balance

- Hold function
- Full range tare
- Zero Tracking
- Large backlit LCD display
- Four load cell construction
- Wall mount bracket
- Large stainless steel platform
- Modern low profile design
- Splashproof to protect from accidental spills
- Simple 4 button operation
- Tare function
- Wheels to allow easy movement
- RS-232 bi-directional interface
- External calibration
- Rechargeable battery
- Auto sleep / power down function to save battery life
- Low battery indication
- DC Adapter
- Animal / dynamic weighing
- Weighing



## Technical Specifications

Model	CPWplus 35L.	CPWplus 75L.	CPWPlus	CPWPlus	CPWPlus
Maximum capacity	75lb/35kg	165lb/75kg	330lb/150kg	440lb/200kg	660lb/300kg
Readability	0.02lb/10g	0.05lb/20g	0.1lb/50g	0.1lb/50g	0.2lb/100g
Repeatability (S.D.)	0.02lb / 10g	0.05lb / 20g	0.1lb / 50g	0.1lb / 50g	100g
Linearity (±)	0.04lb / 20g	0.1lb / 40g	0.2lb / 100g	0.2lb / 100g	200g
Pan size	35.4 x 23.6" / 900 x 600mm				

## General Specifications

Typical stabilisation time	2-3 Sec
Units of measurement	Kilogram (kg), Pound (lb), Ounce (Oz), Pound-Ounce (lb-oz)
Interface	RS-232 bi-directional Interface
Operating temperature	32°F - 104°F
Calibration	Automatic External with user selectable calibration mass
Display	LCD with minimum 22mm digits with weight legends for kg, lb, oz and low battery, stable, zero, net weight and hold symbols, as well as ability to display lb and oz together
Housing	Indicator- Aluminium, Platform- Mild Steel base and stainless steel platform
Dimensions notes	Indicator: 220 x 95 x 43mm (w x d x h)
Net weight	31.7lb

## Key Accessories

- RS-232 to PC Cable
- Adam DU - Data Collection Program
- Rubber non-slip mat for CPWplus L
- RS-232 to USB Interface Cable (must be ordered in conjunction)
- ATP Thermal Printer
- Thermal Paper For Adam ATP (10 pack)



Adam Equipment - offices worldwide

[www.adamequipment.com](http://www.adamequipment.com)