

Heliflex® AT™-1

- Excellent general purpose columns
- Similar to DB-1, Rtx®-1, SPB™-1, SPB™-Sulfur, SP-2100, HP-1, HP-101, ULTRA-1, BP-1, CP-Sil 5CB, 007-1, OV-1, SE™-30, DC-200, RSL-150, RSL-160, PE-1, ZB-1



Heliflex® AT™-1 Specifications

Phase:	100% Dimethylpolysiloxane
Polarity:	Non-polar General Purpose Column
USP Designation:	G1, G2, G38
Ideal For:	General Purpose

Heliflex® AT™-1 Capillary Columns

Length	i.d.	Film	Temp. Limits min.–max.	Part No.
10m	0.25mm	0.20µm	-60–350°C	932510
	0.32mm	0.10µm	-60–350°C	16868
	0.32mm	0.25µm	-60–350°C	13755
	0.32mm	0.30µm	-60–350°C	933210
	0.53mm	0.25µm	-60–350°C	16840
	0.53mm	1.20µm	-60–350°C	935110
	0.53mm	2.65µm	-60–300°C	16849
	0.53mm	5.00µm	-60–300°C	16842
15m	0.25mm	0.10µm	-60–350°C	13649
	0.25mm	0.25µm	-60–350°C	13753
	0.25mm	1.00µm	-60–350°C	13653
	0.32mm	0.10µm	-60–350°C	13673
	0.32mm	0.25µm	-60–350°C	13757
	0.32mm	1.00µm	-60–350°C	13698
	0.32mm	5.00µm	-60–300°C	16836
	0.53mm	0.15µm	-60–350°C	13945
	0.53mm	1.20µm	-60–350°C	935115
	0.53mm	1.50µm	-60–330°C	13905
	0.53mm	3.00µm	-60–300°C	13893
	0.53mm	5.00µm	-60–300°C	16851
25m	0.25mm	0.20µm	-60–350°C	932525
	0.32mm	0.30µm	-60–350°C	933225
30m	0.25mm	0.10µm	-60–350°C	13663
	0.25mm	0.25µm	-60–350°C	13638
	0.25mm	1.00µm	-60–350°C	13639
	0.32mm	0.25µm	-60–350°C	13640
	0.32mm	0.30µm	-60–350°C	933230
	0.32mm	1.00µm	-60–350°C	13641
	0.32mm	3.00µm	-60–300°C	13702
	0.32mm	5.00µm	-60–300°C	16838
	0.53mm	0.50µm	-60–350°C	14038
	0.53mm	1.00µm	-60–350°C	13515
	0.53mm	1.20µm	-60–350°C	935130
	0.53mm	1.50µm	-60–330°C	13908
30m	0.53mm	2.65µm	-60–300°C	16876
	0.53mm	3.00µm	-60–300°C	13897
	0.53mm	5.00µm	-60–300°C	16843
50m	0.25mm	0.20µm	-60–350°C	932550
60m	0.25mm	0.25µm	-60–350°C	13666
	0.25mm	1.00µm	-60–350°C	13667
	0.32mm	0.10µm	-60–350°C	13700
	0.32mm	1.00µm	-60–350°C	13669
	0.32mm	3.00µm	-60–300°C	13703
	0.32mm	5.00µm	-60–300°C	13704
	0.53mm	3.00µm	-60–300°C	13902
	0.53mm	5.00µm	-60–300°C	13810
100m	0.25mm	0.25µm	-60–350°C	13972

Econo-Cap™ EC™-1

- Batch tested to dramatically reduce price



Econo-Cap™ EC™-1 Capillary Columns

Length	i.d.	Film	Temp. Limits min.–max.	Part No.
30m	0.25mm	0.25µm	-60–350°C	19652
	0.32mm	0.25µm	-60–350°C	19651
	0.32mm	1.00µm	-60–350°C	19660
	0.53mm	1.20µm	-60–350°C	19656

Econo-Cap™ EC™-1 Capillary Columns, Six Pack

Length	i.d.	Film	Temp. Limits min.–max.	Part No.
30m	0.25mm	0.25µm	-60–350°C	196526
30m	0.32mm	0.25µm	-60–350°C	196516
30m	0.53mm	1.20µm	-60–350°C	196566

