

Hotplates

Heating baths | Accessories



C-MAG HP 7

Elevated control panel for protection against spilled liquids

Hot top indicator to prevent burns

LED digital display for precise temperature setting



Technical data	
Temperature display	digital
Heat output	250 W
Heating rate	2.5 K/min
Temperature range	50 – 500 °C
Setting accuracy	± 5 K
Safety circuit fixed	550 °C
Control accuracy with sensor	–
Heating plate material	glass ceramic
Weight	3 kg
Dimensions (W x D x H)	150 x 260 x 105 mm

C-MAG HP 4	
Temperature display	digital
Heat output	250 W
Heating rate	2.5 K/min
Temperature range	50 – 500 °C
Setting accuracy	± 5 K
Safety circuit fixed	550 °C
Control accuracy with sensor	–
Heating plate material	glass ceramic
Weight	3 kg
Dimensions (W x D x H)	150 x 260 x 105 mm
Ident. No.	0003581600

C-MAG HP 7	
Temperature display	digital
Heat output	1000 W
Heating rate	5 K/min
Temperature range	50 – 500 °C
Setting accuracy	± 5 K
Safety circuit fixed	550 °C
Control accuracy with sensor	ETS-D5 / ± 0.5 K
Heating plate material	glass ceramic
Weight	5 kg
Dimensions (W x D x H)	220 x 330 x 105 mm
Ident. No.	0003581800

C-MAG HP 10	
Temperature display	digital
Heat output	1500 W
Heating rate	5 K/min
Temperature range	50 – 500 °C
Setting accuracy	± 5 K
Safety circuit fixed	550 °C
Control accuracy with sensor	ETS-D5 / ± 0.5 K
Heating plate material	glass ceramic
Weight	6 kg
Dimensions (W x D x H)	300 x 415 x 105 mm
Ident. No.	0003582000



Technical data	
Heat output	1.300 W
Temperature range	RT – 180 °C
Setting tolerance	± 1 K
Deviation (3 l H ₂ O, 90 °C)	± 1 K
Temperature display	digital
Safety class acc. to DIN 12877	2
Adjustable safety circuit min / max	50 °C / 190 °C
Material	stainless steel 1.4301
Weight	3 kg
Dimensions (W x D x H)	290 x 190 x 265 mm

HB 10	
Heat output	1.300 W
Temperature range	RT – 180 °C
Setting tolerance	± 1 K
Deviation (3 l H ₂ O, 90 °C)	± 1 K
Temperature display	digital
Safety class acc. to DIN 12877	2
Adjustable safety circuit min / max	50 °C / 190 °C
Material	stainless steel 1.4301
Weight	3 kg
Dimensions (W x D x H)	290 x 190 x 265 mm
Ident. No.	0004068000

HBR 4 digital	
Heat output	1000 W
Temperature range	RT – 200 °C
Setting tolerance	± 1 K
Deviation (3 l H ₂ O, 90 °C)	± 1 K
Temperature display	digital
Safety class acc. to DIN 12877	2
Adjustable safety circuit min / max	–
Material	stainless steel (AISI 304)
Weight	4.4 kg
Dimensions (W x D x H)	–
Ident. No.	0002602300

HBR 4 digital accessories	
Ident. No.	
H 240	0002858700
Ring set	
H 159	0001809700
Intermediate bottom	

