

OV[®]-1301 (6% Cyanopropylphenyl Methylpolysiloxane)

Features

- Low to Mid Polarity
- Bonded and Crosslinked
- Solvent Rinsable
- Equivalent to USP Phase G43


Applications

- Volatile Organics
- Pharmaceutical Samples
- Alcohols
- Oxygenates
- Pesticides
- Aroclors
- PCB's

ID	Film Micron	Temperature Limit (Celsius)	15 Meter	30 Meter	60 Meter
0.25mm	0.10	-20 to 280/300	815-2501	830-2501	860-2501
0.25mm	0.25	-20 to 280/300	815-2502	830-2502	860-2502
0.25mm	0.50	-20 to 280/300	815-2503	830-2503	860-2503
0.25mm	1.00	-20 to 280/300	815-2504	830-2504	860-2504
0.32mm	0.10	-20 to 280/300	815-3201	830-3201	860-3201
0.32mm	0.25	-20 to 280/300	815-3202	830-3202	860-3202
0.32mm	0.50	-20 to 280/300	815-3203	830-3203	860-3203
0.32mm	1.00	-20 to 280/300	815-3204	830-3204	860-3204
0.53mm	0.10	-20 to 260/280	815-5301	830-5301	860-5301
0.53mm	0.25	-20 to 260/280	815-5302	830-5302	860-5302
0.53mm	0.50	-20 to 260/280	815-5303	830-5303	860-5303
0.53mm	1.00	-20 to 260/280	815-5304	830-5304	860-5304
0.53mm	1.50	-20 to 260/280	815-5310	830-5310	860-5310
0.53mm	3.00	-20 to 260/280	815-5311	830-5311	860-5311

Similar Phases

- DB-1301
- HP-1301
- PE-1301
- Rtx-1301




OV[®]-1701 (14% Cyanopropylphenyl Methylpolysiloxane)

Applications

- Pharmaceutical Samples
- Alcohols
- Oxygenates
- Pesticides
- Aroclors
- PCBs
- Solvents

Similar Phases

- BP-10
- CB-1701
- CP-Sil 19CB
- DB-1701
- Rtx-1701



ID	Film Micron	Temperature Limit (Celsius)	15 Meter	30 Meter	60 Meter
0.25mm	0.10	-20 to 280/300	415-2500	430-2500	460-2500
0.25mm	0.15	-20 to 280/300	415-2501	430-2501	460-2501
0.25mm	0.25	-20 to 280/300	415-2502	430-2502	460-2502
0.25mm	0.50	-20 to 280/300	415-2503	430-2503	460-2503
0.25mm	1.00	-20 to 280/300	415-2504	430-2504	
0.32mm	0.10	-20 to 280/300	415-3200	430-3200	460-3200
0.32mm	0.15	-20 to 280/300	415-3201	430-3201	
0.32mm	0.25	-20 to 280/300	415-3202	430-3202	460-3202
0.32mm	0.50	-20 to 280/300	415-3203	430-3203	460-3203
0.32mm	1.00	-20 to 280/300	415-3204	430-3204	460-3204
0.53mm	0.10	-20 to 260/280	415-5300	430-5300	460-5300
0.53mm	0.25	-20 to 260/280	415-5302	430-5302	460-5302
0.53mm	0.50	-20 to 260/280	415-5303	430-5303	460-5303
0.53mm	1.00	-20 to 260/280	415-5310	430-5310	460-5310
0.53mm	1.50	-20 to 260/280	415-5311	430-5311	460-5311