

OV[®]-20 (20% Diphenyl, 80% Dimethylpolysiloxane)

Features


- Low to Mid Polarity
- Bonded and Crosslinked
- Solvent Rinsable

Applications

- Alcoholic Beverages
- Flavor Aromatics
- Volatile Compounds

Similar Phases

- DB-20
- Rtx-20
- SPB-20
- VOCOL



ID	Film Micron	Temperature Limit (Celsius)	15 Meter	30 Meter	60 Meter
0.25mm	0.10	-20 to 300/320	2015-2501	2030-2501	2060-2501
0.25mm	0.25	-20 to 300/320	2015-2502	2030-2502	2060-2502
0.25mm	0.50	-20 to 290/310	2015-2503	2030-2503	2060-2503
0.25mm	1.00	-20 to 280/300	2015-2504	2030-2504	2060-2504
0.32mm	0.10	-20 to 300/320	2015-3201	2030-3201	2060-3201
0.32mm	0.25	-20 to 300/320	2015-3202	2030-3202	2060-3202
0.32mm	0.50	-20 to 290/310	2015-3203	2030-3203	2060-3203
0.32mm	1.00	-20 to 280/300	2015-3204	2030-3204	2060-3204
0.32mm	3.00	-20 to 250/270	2015-3205	2030-3205	2060-3205
0.53mm	0.10	-20 to 260/280	2015-5301	2030-5301	2060-5301
0.53mm	0.25	-20 to 260/280	2015-5302	2030-5302	2060-5302
0.53mm	0.50	-20 to 260/280	2015-5303	2030-5303	2060-5303
0.53mm	1.00	-20 to 260/280	2015-5304	2030-5304	2060-5304
0.53mm	1.50	-20 to 250/270	2015-5310	2030-5310	2060-5310
0.53mm	3.00	-20 to 240/260	2015-5311	2030-5311	2060-5311

OV[®]-35 (35% Diphenyl, 65% Dimethylpolysiloxane)

Features


- Mid Polarity
- Bonded and Crosslinked
- Low Bleed
- Equivalent to USP Phase G42
- Solvent Rinsable

Applications

- Aroclors
- Pesticides
- Pharmaceuticals

Similar Phases

- AT-35
- PE-35
- SPB-35
- Rtx-35
- DB-35
- HP-35



ID	Film Micron	Temperature Limit (Celsius)	15 Meter	30 Meter	60 Meter
0.25mm	0.10	40 to 300/320	3515-2500	3530-2500	3560-2500
0.25mm	0.25	40 to 300/320	3515-2502	3530-2502	3560-2502
0.25mm	0.50	40 to 300/320	3515-2503	3530-2503	3560-2503
0.25mm	1.00	40 to 280/300	3515-2504	3530-2504	3560-2504
0.32mm	0.10	40 to 300/320	3515-3200	3530-3200	3560-3200
0.32mm	0.25	40 to 300/320	3515-3202	3530-3202	3560-3202
0.32mm	0.50	40 to 300/320	3515-3203	3530-3203	3560-3203
0.32mm	1.00	40 to 300/320	3515-3204	3530-3204	3560-3204
0.32mm	1.50	40 to 280/300	3515-3210	3530-3210	3560-3210
0.53mm	0.10	40 to 280/300	3515-5300	3530-5300	3560-5300
0.53mm	0.25	40 to 280/300	3515-5302	3530-5302	3560-5302
0.53mm	0.50	40 to 280/300	3515-5303	3530-5303	3560-5303
0.53mm	1.00	40 to 280/300	3515-5304	3530-5304	3560-5304
0.53mm	1.50	40 to 260/280	3515-5310	3530-5310	3560-5310

ID	Film Micron	Temperature Limit (Celsius)	15 Meter	30 Meter
0.45mm	0.42	40 to 300/320		3530-4542
0.45mm	0.85	40 to 280/300	3515-4585	3530-4585